## All About Your Data

### PROMISE TECHNOLOGY, INC

# SuperTrak® EX SAS and SATA RAID Controllers



#### **Enterprise-Class RAID Reliability**

SuperTrak EX SAS and SATA RAID controllers are stable, robust platforms that can be trusted. Built on a leading edge hardware design, supported by a RAID stack developed and refined over more than 15 years, they incorporate a single chip solution for optimized reliability with 512MB data cache on-board, an available 72 hour battery backup module, and a x8 PCI-Express interface to the host.

The SuperTrak EX line of SAS and SATA RAID controllers, with RAID 5 and RAID 6 support, protects your mission-critical data by delivering the data protection features you expect from leadership solutions. Features such as global and dedicated hot spares, RAID level migration, media patrol, read check table, and bad sector remapping offer the most reliable data protection solutions in their class.

#### **Easy Management**

The new web-based Promise Array Manager Professional (WebPAM™ PRO) makes SuperTrak RAID Controllers easy to manage for both Windows and Linux environments through the browser-based graphical user interface to create, delete, expand, and convert disk arrays from anywhere in the world.

In the event of a drive or data path failure, WebPAM PRO supports an array of notification options including text and email, as well as an audio alarm located directly on the STEX RAID controller.

#### **SAS RAID Controllers for Performance Hungry Storage**

The SuperTrak SAS and SATA RAID controllers are high-performance solutions delivering reliability to demanding data-intensive applications such as tiered storage environments (disk-to-disk or disk-to-disk-to-tape backup), security and surveillance, video editing, and digital content creation.

Support for both SAS and SATA 3Gb/s drives on the same controller maintains configuration optimization for performance based on the characteristics of SAS and SATA drives available today. It's like getting SAS for free.



- :: 3Gb/s SAS/SATA
- :: Hardware-accelerated RAID 6 maximum data protection
- :: Supports RAID levels 0, 1, 1E, 5, 6, 10, 50, 60
- PerfectRAID<sup>™</sup> technology for robust error handling and recovery
- :: Automatic/manual rebuild of dedicated and global hot spare drive
- :: Online capacity expansion and RAID level migration to add capacity as needed
- :: Optional 72 hour battery backup module
- :: Linux Open Source driver support
- :: Multiple logical drive support
- :: Intel IOP348 Dual XScale I/O processor
- :: PCI Express x8 Host Bus Interface





















#### **Sophisticated Array Management Tools**

. C. O. E. Camire	onthin in the way	ampac.	en la mineral	derden, kara	-Brusely			6 - b 12-		
MIST	tupa	*	Mirchell			twent   Contact	im   Lagra		a principal parties	ar at co caca cranged
· Exerumental start	W0, W8,74,74	ten tray								100
and an about	Monthle	Name of	Canadian	Belonical	Kaban	ochano i				
Der Rengeleit	COMPANIES.							_		
Linyanoromanoprom	Distance of									
Internationaport	The Control of the Co			Belon						
	inners he			-						
7 000a										
	No limitana			pio hos						
	market.									
	rise .			Drawn						
d follows?	Name of Physics Invest									
	Number of Lags of Street									
H D Population	Available Available			PH 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4						
DBH IDNATUTIONS										
SHIP STEADARD STORTAGE						Terr				
San + (Evoluta Saltistano)								County do 710		
Openional Company	51		ST KINDA			54/4		04750	in, Faunti	
Observation of the last of the	ISSE BONGS				540		2.000			
On-common						540		T-000	-	
Ege res	NAME OF TAXABLE PARTY O							2000		
State and Admin	PLOS		PERMIT			tara.		T-ETE	-	
	C-Toront Last									
Million (ne.)							1000	and the last		
2 territors				BARR .		- 366 4		- Total 40	w South	
23 toenine k	THE R. P. LEW.	_	344		R. See		Beach	man's breast		
Ligitalimetersory	40.48 M M M					207 11 2 10 1				
#(spotters)	10 H 3 K				ORIG NO			CONTRACTOR STANCE		
<b>B</b> LIPHONE	SCHOOL STATE				W 100			or or ow their		
Biantima	TO THE R. (IN)				CERT INC			OF THE PROPERTY.		
	1018 8 20								Sin Date with	
			WEATHER THE		OTHER DATE			Brit treffed to		
			SW Flore Date		WR 101			service foliate		

Web-based Promise Array Management (WebPAM PRO) software offers professional management tools in a simple-to-use, straightforward format. Array configurations, management and monitoring features are available via the web-based interface. Moreover, the SuperTrak EX family supports industry standard SNMP and CIM/WBEM so third party management application integration is simplified.

### A Leader in SAS and SATA RAID

Promise Technology is the originator of ATA RAID and is a worldwide leader in SAS/SATA RAID with over 15 million controllers shipped. Using SAS and SATA technology to design and manufacture fast, reliable, cost-effective data protection, Promise is the preferred choice for SAS/SATA host bus adapters, RAID controllers and SAS/SATA external storage systems.

Specifications							
Model	STEX16650						
Features							
Controller Configuration	16 internal SAS/SATA ports at 3Gbps     Four SAS SFF-8087 connectors     1.2Ghz Intel 81348 XScale I/O processor     Onboard 512MB ECC DDRII memory						
Hardware Features	<ul> <li>PCI-Express x8 host bus interface</li> <li>Hardware XOR engine to offload parity calculation</li> <li>Hardware RAID 6 accelerator</li> <li>Full Height MD2 form factor</li> <li>Optional on-board battery backup unit for data retention up to 72 hours</li> </ul>						
Supported RAID Levels	<ul> <li>RAID 0 - Data striped across 1-16 drives for increased performance, but no data protection</li> <li>RAID 1 - Mirrored pair of drives for data protection with increased read performance</li> <li>RAID 1E - Data mirroring extended to maximize balanced performance. Allows odd number drive mirroring</li> <li>RAID 5 - Striped parity on 3-16 drives, ultimate data protection, capacity and performance balance</li> <li>RAID 6 - Double parity for maximum data protection on 4-16 drives; allows double drive failures without downtime or data loss</li> <li>RAID 10 - Mirrored pair of RAID 0 for double drive failure protection; can be split into two RAID 0 sets</li> <li>RAID 50 - Striped multiple RAID 5 sets to improve performance and provide additional data protection</li> <li>RAID 60 - Striped multiple RAID 6 sets to allow multiple drive failures to achieve high-data availability</li> </ul>						
RAID Fault Tolerance and Robustness Features	Multiple logical drive support enables combining different RAID levels on one set of disks     Read Check table to avoid data read errors     PerfectRAID™ technology for error handling and recovery of fatal, media and disk errors     Support hot swap of failed drives and hot spares     Automatic/Manual rebuild of hot spare drive     Background initialization for instant drive availability     Supports bad sector remapping     Variable stripe block size support to meet various application requirements     Redundancy Check can be scheduled periodically for RAID data consistency						
Web-based Promise Array Manager	Creates, deletes, expands, and converts disk arrays remotely Media Patrol and Redundancy Check scheduling Monitors drive, array, and enclosure status and provides online event logging Email notification of drive, array, controller or enclosure events (e.g. error or degrade conditions) Remote management based on industry standard CIM/WBEM Interface displays in 10 languages CLI support Remote firmware update						
Operating System Support	Microsoft Windows Vista, 2000, XP, Windows Server 2003, Windows Server 2008     Red Hat Linux, SuSE Linux, Miracle Linux, Fedora Core, Linux open source driver (32/64-bit)     FreeBSD, VMware 3.02, 3.5						
Platform Support	Intel IA32, EM64T, and AMD64						
SuperBuild™ BIOS	<ul> <li>Array configuration utility at the BIOS level</li> <li>BIOS Boot specification support: boot system from any array</li> <li>Flash-upgradeable BIOS for future upgrades</li> </ul>						
Enclosure Management	SES-2     SGPIO     Direct LED support for individual HDD     I <sup>2</sup> C						
Cable in Kit	Four 0.5-meter cables included						
Accessories	Battery Backup Unit PN: STEXBBUIII Cables: www.promise.com/cables						
Operating Temperature	0 to 50°C (40°C w/ BBU) Relative humidity: 5%-95% non-condensing						
Physical Dimensions	16.7 cm x 11.1 cm (6.6" x 4.4")						
Agency Certifications	UL, cUL, CE, FCC Class B, BSMI, VCCI, MIC, C-tick						
Limited Warranty	3 Years						

#### **About Promise**

With a long history of innovation, Promise Technology develops and manufactures sophisticated RAID solutions recognized worldwide, ranging from a complete line of RAID controller cards to SAS/SATA RAID subsystems. Catering to enterprise, midrange and entry-level data protection needs, Promise products are distinguished by their common RAID code, unified management interface and unparalleled support. Known as the originator of SATA/ATA RAID products, Promise's comprehensive product base includes high available (HA) standalone RAID subsystems with standards-based management interfaces, host-based (internal) RAID controllers, NAS appliances for SOHO, and SATA ASICs integrated into an extensive list of industry-leading motherboards. Headquartered in Milpitas, Calif., Promise has operations throughout Asia and Europe. For more information, visit Promise Technology's website at http://www.promise.com

#### :: Promise USA

#### :: Promise EMEA

#### :: Promise Germany

#### :: Promise Italy

Wokingham, United Kingdom
Tel: +44 0 870 112 59 77
E-mail: sales@promise-emea.com

#### :: Promise Taiwan

#### :: Promise China

G6130S166000000-I 08/25/2008

#### :: Promise Japan